

# SAFETY DATA SHEET

## PREMIUM HEALTH GARD AEROSOL DEODORIZER

Infosafe No.: LQ54L  
ISSUED Date : 18/08/2020  
ISSUED by: HOSPECO PTY LTD

### 1. IDENTIFICATION

#### GHS Product Identifier

PREMIUM HEALTH GARD AEROSOL DEODORIZER

#### Company Name

HOSPECO PTY LTD

#### Address

17 Elizabeth Street Wetherill Park  
NSW 2164 AUSTRALIA

#### Telephone/Fax Number

Tel: +61 2 9756 0055

Fax: +61 2 9756 0095

#### Emergency phone number

1800 638 556

#### Recommended use of the chemical and restrictions on use

Air Deodorizer

### 2. HAZARD IDENTIFICATION

#### GHS classification of the substance/mixture

Classified as Hazardous according to the Globally Harmonised System of Classification and Labelling of Chemicals (GHS) including Work, Health and Safety Regulations, Australia.

Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

Eye Damage/Irritation: Category 2A

Flammable Aerosol: Category 1

#### Signal Word (s)

DANGER

#### Hazard Statement (s)

AUH066 Repeated exposure may cause skin dryness or cracking.

H222 Extremely flammable aerosol.

H319 Causes serious eye irritation.

#### Pictogram (s)

Exclamation mark, Flame



**Precautionary statement – Prevention**

P210 Keep away from heat/sparks/open flames/hot surfaces. – No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Pressurized container: Do not pierce or burn, even after use.  
P264 Wash contaminated skin thoroughly after handling.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.

**Precautionary statement – Response**

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337+P313 If eye irritation persists: Get medical advice/attention.

**Precautionary statement – Storage**

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

**Other Information**

This product contains an Ototoxic substance.  
Combination with noise exposure, even at safe levels, could still cause auditory injuries and hearing loss.

Note: Pressurised container may burst if heated.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

---

**Information on Composition**

The product contains less than 0.1 % w/w 1,3-butadiene, Benzene and isoprene.

**Ingredients**

Name	CAS	Proportion
Petroleum gases, liquefied	68476-85-7	0-<45 %
Ethanol	64-17-5	0-<30 %
Distillates, petroleum, hydrotreated light	64742-47-8	0-<30 %
Ingredients determined not to be hazardous		Balance

### 4. FIRST-AID MEASURES

---

**Inhalation**

If inhaled, remove affected person from contaminated area. Keep at rest until recovered. If symptoms develop and/or persist seek medical attention.

**Ingestion**

Unlikely due to form of product. However, if ingested, do not induce vomiting. Wash out mouth thoroughly with water. If symptoms develop seek medical attention.

**Skin**

Remove all contaminated clothing immediately. Wash affected area thoroughly with soap and water. Wash contaminated clothing before reuse or discard. Seek medical attention.

**Eye contact**

If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing for several minutes until all contaminants are washed out completely. Seek medical attention.

**First Aid Facilities**

Eyewash, safety shower and normal washroom facilities.

**Advice to Doctor**

Treat symptomatically.

**Other Information**

For advice in an emergency, contact a Poisons Information Centre (Phone Australia 131 126) or a doctor at once.

## 5. FIRE-FIGHTING MEASURES

---

### Suitable Extinguishing Media

Use foam, dry chemical or carbon dioxide.

### Unsuitable Extinguishing Media

Do not use water.

### Hazards from Combustion Products

Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide and oxides of nitrogen.

### Specific Hazards Arising From The Chemical

Contents under pressure - cans can explode in a fire. This product is extremely flammable. Keep containers and fire-exposed surfaces cool with water spray. Shut off any leak if safe to do so and remove sources of re-ignition. Vapour/air mixtures may ignite explosively. Flashback along the vapour trail may occur. Runoff to sewer may create fire or explosion hazard.

### Hazchem Code

2YE

### Decomposition Temperature

Not available

### Precautions in connection with Fire

Fire fighters should wear full protective clothing and self-contained breathing apparatus (SCBA) operated in positive pressure mode. In case of fire the product may be violently or explosively reactive. Use water spray to disperse vapours. This product should be prevented from entering drains and watercourses.

## 6. ACCIDENTAL RELEASE MEASURES

---

### Emergency Procedures

Extinguish or remove all sources of ignition and stop leak if safe to do so. Wear appropriate personal protective equipment and clothing to prevent exposure. Evacuate all unprotected personnel. Water spray or fog may be used to disperse/absorb vapour if any. Place inert, non-combustible absorbent material onto spillage. If safe, damaged cans should be placed in a container outdoors, away from ignition sources, until pressure has dissipated. Undamaged cans should be gathered and stowed safely. Collect residues and seal in labelled drums for disposal. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations. Dispose of waste according to applicable local and national regulations.

## 7. HANDLING AND STORAGE

---

### Precautions for Safe Handling

FLAMMABLE. VAPOUR OR GAS REDUCES OXYGEN FOR BREATHING. IN CONFINED SPACES MAY CAUSE ASPHYXIATION. Wear appropriate personal protective equipment and clothing to prevent exposure. Handle and use the material in a well-ventilated area, away from sparks, flames and other ignition sources. DO NOT store or use in confined spaces. Have emergency equipment (for fires, spills, leaks, etc.) readily available. Build up of mists or vapours in the atmosphere must be prevented. Do NOT cut or heat containers as they may contain hazardous residues. Do not smoke. Flameproof equipment is necessary in areas where the product is being used. Take precautionary measures against static discharges. Earth or bond all equipment. Do not empty into drains. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands before eating, drinking, smoking or using the toilet facilities.

### Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated area away from sources of ignition, oxidising agents, foodstuffs, clothing and out of direct sunlight. Do not expose can to temperatures exceeding 50°C. Protect containers against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Do NOT pressurise, cut or heat aerosol containers. Content is under pressure and can explode violently. Ensure that storage conditions comply with applicable local and national regulations.

For information on the design of the storeroom, reference should be made to Australian Standard AS 2278.1. Non-refillable metal aerosol dispensers of capacity 50 mL to 1000 mL inclusive.

## Storage Temperatures

<=50°C

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

### Occupational exposure limit values

No exposure standards have been established for this material. However, the available exposure limits for ingredients are listed below:

Ethanol

TWA: 1000 ppm, 1880 mg/m<sup>3</sup>

Liquified Petroleum gas

TWA: 1000 ppm, 1800 mg/m<sup>3</sup>

Notices: Carc.1A

Oil mist, refined mineral

TWA: 5 mg/m<sup>3</sup>

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

Carc.1A: Known to have carcinogenic potential for humans.

Source: Safe Work Australia

### Biological Limit Values

No biological limits allocated.

### Appropriate Engineering Controls

This substance is hazardous and should be used with a local exhaust ventilation system, drawing vapours away from workers' breathing zone. A flame-proof exhaust ventilation system is required. If the engineering controls are not sufficient to maintain concentrations of vapours/mists below the exposure standards, suitable respiratory protection must be worn. Refer to relevant regulations for further information concerning ventilation requirements.

Refer to AS 2865 Australian Standard Safe working in a confined space, for further information concerning ventilation requirements.

### Respiratory Protection

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements.

Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

### Eye Protection

Safety glasses with side shields, chemical goggles or full-face shield as appropriate should be used. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform to relevant regulations.

Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 (series) - Eye Protectors for Industrial Applications.

### Hand Protection

Wear gloves of impervious material such as rubber. Final choice of appropriate gloves will vary according to individual circumstances. i.e. methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations.

Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

### Body Protection

Suitable protective work wear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

### Other Information

Liquified Petroleum gas is an asphyxiant gas which when present in an atmosphere in high concentration, leads to reduction of oxygen concentration by displacement or dilution. It is not appropriate to recommend an exposure standard for each simple asphyxiant, rather it should be required that a sufficient oxygen concentration be maintained.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Properties	Description	Properties	Description
Form	Aerosol	Appearance	Aerosol
Colour	Not available	Odour	Not available
Decomposition Temperature	Not available	Melting Point	Not available
Boiling Point	-42°C - 254.4°C	Solubility in Water	Miscible
Specific Gravity	0.6746	pH	Not available
Vapour Pressure	Not available	Vapour Density (Air=1)	Heavier than air
Evaporation Rate	Not available	Odour Threshold	Not available
Viscosity	Not available	Partition Coefficient: n-octanol/water	Not available
Density	Not available	Flash Point	Not available
Flammability	Extremely flammable aerosol	Auto-Ignition Temperature	Not available
Flammable Limits - Lower	Not available	Flammable Limits - Upper	Not available

## 10. STABILITY AND REACTIVITY

### Reactivity

Not available

### Chemical Stability

Stable under normal conditions of storage and handling.

### Conditions to Avoid

Heat, direct sunlight, flames and other sources of ignition.

### Incompatible materials

Strong oxidising agents.

### Hazardous Decomposition Products

Thermal decomposition may result in the release of toxic and/or irritating fumes, smoke and gases including: carbon dioxide and carbon monoxide.

### Possibility of hazardous reactions

Not available

### Hazardous Polymerization

Will not occur.

## 11. TOXICOLOGICAL INFORMATION

### Toxicology Information

No toxicity data available for this material.

### Ingestion

Unlikely due to form of product. If ingestion occurs, may cause irritation to the gastrointestinal system. Symptoms may include nausea, vomiting, diarrhoea and abdominal pain.

### Inhalation

Inhalation of product vapours may cause irritation of the nose, throat and respiratory system.

Liquified Petroleum gas is an asphyxiant gas which when present in an atmosphere in high concentration, leads to reduction of oxygen concentration by displacement or dilution. Symptoms include decreased visual acuity, decreased coordination and judgment, headache, dizziness, confusion, drowsiness, fatigue, shortness of breath, muscular weakness, convulsions, unconsciousness, coma and eventually death.

**Skin**

May be irritating to skin. The symptoms may include redness and itching. Repeated exposure may cause skin dryness and cracking and may lead to dermatitis.

**Eye**

Causes serious eye irritation. On eye contact this product will cause tearing, stinging, blurred vision, and redness.

**Respiratory sensitisation**

Not expected to be a respiratory sensitiser.

**Skin Sensitisation**

Not expected to be a skin sensitiser.

**Germ cell mutagenicity**

Not considered to be a mutagenic hazard.

**Carcinogenicity**

Not considered to be a carcinogenic hazard.

**Reproductive Toxicity**

Not considered to be toxic to reproduction.

**STOT-single exposure**

Not expected to cause toxicity to a specific target organ.

**STOT-repeated exposure**

Not expected to cause toxicity to a specific target organ.

**Aspiration Hazard**

Not expected to be an aspiration hazard.

**Other Information**

This product contains an Ototoxic substance.

Combination with noise exposure, even at safe levels, could still cause auditory injuries and hearing loss.

## 12. ECOLOGICAL INFORMATION

---

**Ecotoxicity**

No ecological data available for this material.

**Persistence and degradability**

Not available

**Mobility**

Not available

**Bioaccumulative Potential**

Not available

**Other Adverse Effects**

Not available

**Environmental Protection**

Do not discharge this material into waterways, drains and sewers.

## 13. DISPOSAL CONSIDERATIONS

---

**Disposal considerations**

Dispose of waste according to applicable local and national regulations. Do not pierce, burn, cut, puncture or weld on or near containers. Empty containers may contain hazardous residues. Empty the container completely before disposal. Contaminated containers must not be treated as household waste. Advise flammable nature.

## 14. TRANSPORT INFORMATION

---

**Transport Information**

Road and Rail Transport (ADG Code):

This material is classified as Dangerous Goods Division 2.1 Flammable Gases

Division 2.1 Dangerous Goods are incompatible in a placard load with any of the following:

- Class 1: Explosives
- Division 2.2 Non-flammable, Non toxic gas that have a subsidiary risk 5.1 except when all are packed in cylinders or pressure drums not exceeding 500L capacity.
- Class 3: Flammable Liquids, if both the Division 2.1 and Class 3 dangerous goods are in tanks or other receptacles with a capacity individually exceeding 500L.
- Division 4.1: Flammable Solids
- Division 4.2: Spontaneously combustible substances
- Division 4.3: Dangerous when wet substances
- Division 5.1: Oxidising substances
- Division 5.2: Organic peroxides
- Class 7: Radioactive materials unless specifically exempted

Marine Transport (IMO/IMDG):

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

Proper Shipping Name: AEROSOLS

UN-No: 1950

Division: 2.1

EmS: F-D,S-U

Special Provisions: 63, 190, 277, 327, 344, 381, 959

Air Transport (ICAO/IATA):

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

Proper Shipping Name: AEROSOLS, flammable

UN-No: 1950

Division: 2.1

Label: Flammable Gas

Packaging Instructions (cargo only): 203

Packaging Instructions (passenger & cargo): 203

Special Provisions: A145, A167, A802

**U.N. Number**

1950

**UN proper shipping name**

AEROSOLS

**Transport hazard class(es)**

2.1

**Hazchem Code**

2YE

**IERG Number**

49

**IMDG Marine pollutant**

No

**Transport in Bulk**

Not available

**Special Precautions for User**

Not available

## 15. REGULATORY INFORMATION

---

**Regulatory information**

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.

Not classified as a Scheduled Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

## Poisons Schedule

Not Scheduled

## 16. OTHER INFORMATION

---

### Date of preparation or last revision of SDS

SDS reviewed: August 2020 SDS superseded: November 2016

### References

Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.  
Standard for the Uniform Scheduling of Medicines and Poisons.

Australian Code for the Transport of Dangerous Goods by Road & Rail.

Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.

Workplace exposure standards for airborne contaminants.

Adopted biological exposure determinants, American Conference of Industrial Hygienists (ACGIH).

Globally Harmonised System of Classification and Labelling of Chemicals.

Code of Practice: Managing Noise and Preventing Hearing Loss at Work.

## END OF SDS

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

The compilation of SDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any SDS displayed is permitted for personal use only and otherwise is not permitted. In particular the SDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of SDS without the express written consent of Chemical Safety International Pty Ltd.