



Speedshine 1500E Ultra High

Speed Vacuum Floor Burnisher - 1500rpm

Ideal for large floor surfaces.

The Speedshine 1500E has a true center mount drive motor with a direct drive. This offers a balanced ease of use, that leaves the operator in control and maximizes performance. The drive system does not require maintenance or adjustments.

Quality is built into all the components, including stainless steel handle, axle and all fasteners.

The motor has a fin aluminum chassis, fan cooled that allows for the coolest running motor on the market. The engineering shows through with the motor hub that drives the pad driver and acts as a heat sink for the motor shaft, this helps to keep the motor cooler

The vacuum system is fully enclosed and mounted on the base of the machine.

The vacuum system is fully enclosed so dust does not escape as in bag fill machines and no debris passes through the fan that can cause damage and bearing wear.

Designed with a tough plastic cover that protects the motor and components like the capacitors. It also keeps the machine looking good with its clean lines and durability.





















Easy to





Gloss **Floors**

Scan to discover! nload this free Unitag App to scan at unitag.io/app

- 1) A cam lever locks the handle with ease for **Operator comfort**
 - 5) A 52.5cm pad is standard for greater peripheral speed for a better result.
- 2) Ergonomically designed control handle that is made safe with flame retardant materials
- 6) 150mm double ball bearing non marking wheels for easy transport.
- 3) A robust injection molded cover that improves cooling and protects the motor.
- 7) A sealed vacuum system, with optional disposable dust bag.
- 4) Ergonomic switch levers that allow the load to be spread over the whole hand
- 8) Variable Brush pressure adjustments to suit all Floor burnishing requirements.

Technica l	Specifications

Motor 4 pole, 1.5K (2Hp) Aluminium Fin chassis, fan cooled **Brush Drive** Direct Pad Speed 1440 RPM Pad Size 52.5 cm, adjustable pad pressure Fully sealed canister with optional disposable bags. Clear lid. Vacuum System Thermal cutout Vacuum Motor 250W 1 stage fan Flow-thru **Filtration** 4 stage filtration 99.98% at 0.3 micron Filter Bag capacity 3L Handle Fully Adjustable Lead 15M Heavy Duty, Rubber with cable restraint Wheels 150mm double bearing, rated 300Kgs Weight 50 Kg

Optional disposable dust bags

Make disposing of collected dust clean and easy

> **Hako Australia Pty Ltd** www.hakoaustralia.com.au

hksales@hakoaustralia.com.au Phone: 1800 257 221